

**ICC-ES PMG Listing****PMG-1005***Effective Date: March 1, 2011**This listing is subject to re-examination in one year***www.icc-es.org/pmg | (800) 423-6587 | (562) 699-0543***A Subsidiary of the International Code Council®*CSI: DIVISION: 09 00 00—FINISHES  
Section: 09 30 00—Tiling

## Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system

Product: LATICRETE 9235 Waterproofing Membrane

Listee: LATICRETE International, Inc.  
1 Laticrete Park North  
Bethany, Connecticut 06524-3423  
[www.laticrete.com](http://www.laticrete.com)

## Compliance with the following codes:

2006, 2009, and 2012 *International Residential Code*® (IRC)  
2006, 2009, and 2012 *International Plumbing Code*® (IPC)  
2006, and 2009 *Uniform Plumbing Code* (UPC)  
1997 *Standard Plumbing Code*® (SPC)

## Compliance with the following standard:

ANSI A 118.10-2008

## Identification:

Each container of LATICRETE 9235 liquid membrane, reinforcement fabric, sealant and reinforcement tape described in this listing must be identified by a stamp bearing the manufacturer's name (LATICRETE International, Inc.), the product type, and either the ICC-ES evaluation report number (ESR-1058) or the ICC-ES PMG listing mark. The ICC-ES PMG listing number (PMG-1005) is optional.

## Installation:

LATICRETE 9235 Waterproofing Membrane must be installed in accordance with the manufacturer's published instructions and the applicable code(s).

Ceramic tile must comply with ANSI A137.1

Drains must have a clamping ring with open weep holes in accordance with ANSI A112.21.1.

Models: LATICRETE 9235 liquid

A ready-to-use, 54-percent-solids, formulated, styrene butadiene, rubber-based latex, packaged in 6-gallon (22.7 L) pails.

LATICRETE 9235 reinforcing fabric

A 2.4-ounce-per-square-yard ( $75.7 \text{ g/m}^2$ ) fabric for use as reinforcement in the LATICRETE 9235 Waterproofing Membrane. The fabric is provided in 300-square-foot ( $27.9 \text{ m}^2$ ) rolls.

LATICRETE 9235 reinforcing tape

A 2.4-ounce-per-square-yard ( $75.7 \text{ g/m}^2$ ) fabric for use in preparing joints and cracks of the substrate before application of the LATICRETE 9235 Waterproofing Membrane. The tape is provided in 6-inch-wide-by-75-foot-long (152 mm by 22 860 mm) rolls.

LATICRETE Latasil Tile and Stone Sealant

A silicone sealant for use with penetrations that come in contact with the LATICRETE 9235 Waterproofing Membrane. The sealant is provided in 10.3-ounce (305 mL) cartridges.

Conditions of Listing:

1. Application is limited to ceramic tile and dimension stone installations on floors, and to use as shower sub-pans or lining.
2. Control joints greater than  $\frac{1}{8}$  inch (3 mm), structural cracks and expansion joints with vertical differential movement used with the LATICRETE 9235 Waterproofing Membrane are outside the scope of this report.