

ICC-ES PMG Listing**PMG-1005**

Reissued: March 1, 2009

*This listing is subject to re-examination in two years.***www.icc-es.org/pmg | (800) 423-6587 | (562) 699-0543***A Subsidiary of the International Code Council®*CSI: DIVISION: 15—MECHANICAL
Section: 15451—Shower Pan Liners

Product: LATICRETE 9235 Waterproofing Membrane

Listee: LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, Connecticut 06524-3423
www.laticrete.com

Compliance with the following codes:

2006 *International Residential Code*® (IRC)
2006 *International Plumbing Code*® (IPC)
2006 *Uniform Plumbing Code* (UPC)
1997 *Standard Plumbing Code*® (SPC)

Compliance with the following standard:

ANSI A 118.10-1999

Identification:

Each container of LATICRETE 9235 liquid membrane, reinforcement fabric, sealant and reinforcement tape described in this listing must be identified by a stamp bearing the manufacturer's name (LATICRETE International, Inc.), the product type, and either the ICC-ES evaluation report number (ESR-1058) or the ICC-ES PMG listing mark. The ICC-ES PMG listing number (PMG-1005) is optional.

Installation:

LATICRETE 9235 Waterproofing Membrane must be installed in accordance with the manufacturer's published instructions and the applicable code(s).

Ceramic tile must comply with ANSI A137.1

Drains must have a clamping ring with open weep holes in accordance with ANSI A112.21.1.

Models: LATICRETE 9235 liquid

A ready-to-use, 54-percent-solids, formulated, styrene butadiene, rubber-based latex, packaged in 6-gallon (22.7 L) pails.

LATICRETE 9235 reinforcing fabric

A 2.4-ounce-per-square-yard (75.7 g/m²) fabric for use as reinforcement in the LATICRETE 9235 Waterproofing Membrane. The fabric is provided in 300-square-foot (27.9 m²) rolls.

LATICRETE 9235 reinforcing tape

A 2.4-ounce-per-square-yard (75.7 g/m²) fabric for use in preparing joints and cracks of the substrate before application of the LATICRETE 9235 Waterproofing Membrane. The tape is provided in 6-inch-wide-by-75-foot-long (152 mm by 22 860 mm) rolls.

LATICRETE Latasil Tile and Stone Sealant

A silicone sealant for use with penetrations that come in contact with the LATICRETE 9235 Waterproofing Membrane. The sealant is provided in 10.3-ounce (305 mL) cartridges.

Conditions of Listing:

1. Application is limited to ceramic tile and dimension stone installations on floors, and to use as shower sub-pans or lining.
2. Control joints greater than $\frac{1}{8}$ inch (3 mm), structural cracks and expansion joints with vertical differential movement used with the LATICRETE 9235 Waterproofing Membrane are outside the scope of this report.