

**ICC-ES PMG Listing****PMG-1049**

Effective Date: September 1, 2009

*This listing is subject to re-examination in one year.***www.icc-es.org/pmg | (800) 423-6587 | (562) 699-0543***A Subsidiary of the International Code Council®*

CSI: DIVISION: 15—MECHANICAL  
Section: 15150—Sanitary Waste and Vent Piping  
Section: 15430—Plumbing Specialties

Product: Thermaco® Trapzilla® Supercapacity Grease Traps

Listee: Thermaco, Inc.  
Post Office Box 2548  
646 Greensboro Street  
Asheboro, North Carolina 27204

Compliance with the following codes:

2009 *International Plumbing Code*® (IPC)  
2009 *IAPMO Uniform Plumbing Code*® (IAPMO UPC)

Compliance with the following standard:

ASME A112.14.3-2000

Identification:

Thermaco® Trapzilla® Supercapacity Grease Traps: The unit and the packaging must be permanently and legibly marked with the manufacturer's name or trademark, model number, inlet, outlet, ASME A112.14.3-2000, product type by rating, efficiency at rated capacity, flow rate, grease capacity, and the ICC-ES PMG listing mark. The ICC-ES PMG listing number is optional on the product.

Installation:

The Trapzilla® Supercapacity Grease Trap is to be installed in accordance with the manufacturer's instructions and the requirements of the IPC and IAPMO UPC. A minimum clearance of 6 inches (152 mm) is to be provided around the lid. Piping connections are to be made using "no hub" connectors. The outlet piping is to be as straight as possible using only sweep connections. The vent is to be installed on the outlet piping.

Models: Trapzilla® Supercapacity Grease Trap consists of the following models for the collection of free-floating (non-emulsified) fats, oils, and grease contained in waste from kitchen fixtures:

TZ-160: The Trapzilla® TZ-160 treats peak kitchen waste flows of 35 gpm (2.21 L/s) and stores up to 167 pounds (75 kg) of free-floating (non-emulsified) fats, oils, and grease.

TZ-400: The Trapzilla® TZ-400 treats peak kitchen waste flows of 75 gpm (4.73 L/s) and stores up to 405 pounds (184 kg) of free-floating (non-emulsified) fats, oils, and grease.

TZ-600: The Trapzilla® TZ-600 treats peak kitchen waste flows of 150 gpm (9.46 L/s) and stores up to 635 pounds (288 kg) of free-floating (non-emulsified) fats, oils, and grease.

Conditions of Listing:

The Thermaco® Trapzilla® Supercapacity Grease Traps must be installed in accordance with the manufacturer's published installation instructions and the applicable code.

*Listings are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the listing or a recommendation for its use. There is no warranty by ICC Evaluation Service, Inc., express or implied, as to any finding or other matter in this listing, or as to any product covered by the listing.*

