

ICC-ES PMG Listing**PMG-1049**

Effective Date: September 01, 2011

This listing is subject to re-examination in one year.

www.icc-es-pmg.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00—PLUMBING
Section: 22 13 16—Sanitary Waste and Vent Piping

Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: Thermaco® Trapzilla® Supercapacity Grease Traps
Thermaco® EZKlear® Grease InterceptorsListee: Thermaco, Inc.
646 Greensboro Street
Asheboro, North Carolina 27204
www.thermaco.com

Compliance with the following codes:

2012, and 2009 *International Plumbing Code*® (IPC)
2009 *Uniform Plumbing Code*® (UPC)*
**Uniform Plumbing Code*® is a registered trademark of IAPMO

Compliance with the following standard:

ASME A112.14.3 Grease Interceptors

Identification:

Thermaco® Trapzilla® Supercapacity Grease Traps, and EZKlear® Grease Interceptors: The unit and the packaging must be permanently and legibly marked with the manufacturer's name or trademark, model number, "Inlet" and "outlet", ASME A112.14.3, product type by rating, efficiency at rated capacity, flow rate, grease capacity, and the ICC-ES PMG listing mark.

Installation:

The Trapzilla® Supercapacity Grease Trap and EZKlear® Grease Interceptors are to be installed in accordance with the manufacturer's instructions and the requirements of the IPC and UPC. A minimum clearance of 6 inches (152 mm) is to be provided around the lid. Piping connections are to be made using "no hub" connectors. The outlet piping is to be as straight as possible using only sweep connections. The vent is to be installed on the outlet piping.

Models: Trapzilla® Supercapacity Grease Trap consists of the following models for the collection of free-floating (non-emulsified) fats, oils, and grease contained in waste from kitchen fixtures:

TZ-160: The Trapzilla® TZ-160 treats peak kitchen waste flows of 35 gpm (2.21 L/s) and stores up to 167 pounds (75 kg) of free-floating (non-emulsified) fats, oils, and grease.

TZ-400: The Trapzilla® TZ-400 treats peak kitchen waste flows of 75 gpm (4.73 L/s) and stores up to 405 pounds (184 kg) of free-floating (non-emulsified) fats, oils, and grease.

TZ-600: The Trapzilla® TZ-600 treats peak kitchen waste flows of 150 gpm (9.46 L/s) and stores up to 635 pounds (288 kg) of free-floating (non-emulsified) fats, oils, and grease.

Listings are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the listing or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this listing, or as to any product covered by the listing.

EZKlear[®] Grease Interceptor consists of the following model for collecting of free-floating (non-emulsified) fats, oils, and grease contained in waste from kitchen fixtures:

EZK-20: The EZKlear[®] EZK-20 treats peak kitchen waster flow of 20 gpm (1.26 L/s) and store upto 40 pounds (18 kg) of free-floating (non-emulsified) fats, oils, and grease.

Conditions of Listing:

1. The Thermaco[®] Trapzilla[®] Supercapacity Grease Traps and EZKlear[®] Grease Interceptors must be installed in accordance with the manufacturer's published installation instructions and the applicable code.
2. The Thermaco[®] Trapzilla[®] Supercapacity Grease Traps and EZKlear[®] Grease Interceptors are manufactured at Accu-Form Polymers in Warsaw, North Carolina, under a quality control program with annual surveillance inspections by QAI Laboratories (AA-723).

