

ICC-ES PMG Listing**PMG-1055**

Effective Date: March 1, 2010

This listing is subject to re-examination in one year.

www.icc-es.org/pmg | (800) 423-6587 | (562) 699-0543 A Subsidiary of the International Code Council®

CSI: DIVISION: 15—MECHANICAL
Section: 15180—Heating and Cooling Piping

Product: Hercules® PVC/CPVC *Un-Purple* Primer

Listee: Hercules Chemical Company, Inc.
111 South Street
Passaic, New Jersey 07055-9100
(800) 221-9330
www.herchem.com

Compliance with the following codes:

2009 *International Plumbing Code*® (IPC)
2009 *International Residential Code*® (IRC)
2009 *International Mechanical Code*® (IMC)
2009 *Uniform Plumbing Code*™* (UPC)
2009 *Uniform Mechanical Code*™* (UMC)

**Uniform Mechanical Code* and *Uniform Plumbing Code* are copyrighted publications of the International Association of Plumbing and Mechanical Officials.

Compliance with the following standards:

ASTM F 656, Standard Specification for Primers for Use in Solvent Cement Joints of Poly Vinyl Chloride (PVC) Plastic Pipe and Fittings
NSF 61, Drinking Water System Components - Health Effects
LC1025, PMG Listing Criteria for Fluorescent Primers

Identification:

Each container of primer must be marked with the following:

- Product name: *Hercules Un-Purple* Primer
- Manufacturing traceability code
- Name of the inspection agency: NSF International (AA-633)
- NSF Standard 61
- ASTM F 656
- ICC-ES PMG listing mark

Installation:

Hercules® PVC/CPVC *Un-Purple* Primer must be installed in accordance with the manufacturer's published installation instructions, which are detailed on the product container label, and the applicable codes.

Models: Hercules® PVC/CPVC *Un-Purple* Primer is a clear, colorless primer for PVC piping. It is supplied in various size containers with self-contained daubers for application of the primer. Under natural light it appears colorless but appears purple under UV “black” light. A UV light source, in good working order, must be supplied by the contractor to the code official or his representative.

Conditions of listing:

1. UV light source, in good working order, must be supplied by the contractor to the code official or his representative.
2. Hercules® PVC/CPVC *Un-Purple* Primer may be used in any location where purple primer is required by the codes.